## **Hole Expansion Tools & Sets**

## STANDARD WOOD AUGERS, HOLE HOG™, DRYWAL BITS

Type 134-AG & Sets

Hole Hog<sup>™</sup> 1/2" Shank 4-Flute Core Drill Super Premium, 3-Flats on Shank

- The 4-flute design eliminates the catching and hogging-in experienced with standard S&D drills when breaking through thinner materials such as truck frames.
- These core drills may replace tapered reamers in many applications.



This tool is designed exclusively for enlarging existing holes.

Part #	Diameter Inches	Minimum Starting Hole Size	OAL Inches	Flute Length Inches	<b>Qty.</b> per/pack
22030	3/8"	1/4"	4-5/16"	1-7/8"	1
22040	1/2"	5/16"	4-5/16"	1-7/8"	1
22060	9/16"	3/8"	4-5/16"	1-7/8"	1
22080	5/8"	25/64"	4-5/16"	1-7/8"	1
22100	11/16"	7/16"	4-5/16"	1-7/8"	1
22120	3/4"	15/32"	4-5/16"	1-7/8"	1

### TYPE 134-AG SETS

## Part# 38880 SP-8HH Set

Contains 1ea:

**134-AG** Core drill sizes: 3/8", 1/2", 5/8" & 3/4" **175-AG** Drill sizes: 1/4", 5/16", 25/64" & 15/32"

#### Part# 38870 SP-6HHL Set Contains 1ea:

**134-AG** <u>Core drill sizes</u>: 1/2", 5/8" & 3/4" **175-AG** <u>Drill sizes</u>: 5/16", 25/64" & 15/32"

#### Part# 38860 SP-6HHS Set Contains 1ea:

**134-AG** <u>Core drill sizes</u>: 3/8", 1/2" & 5/8" **175-AG** <u>Drill sizes</u>: 1/4", 5/16" & 25/64"

A selection of core drills and companion (minimum starting hole size) pilot drills in a black steel index.

## **DRYWALL BITS FOR CUTOUTS**

## Type 180-GP - Black & Gold

High-Speed Steel - Guide Point Left-Hand Cut

- · Cuts material Up to 1" thick
- Left-hand spiral, Right hand cut.
- · For use with Rotozip Spiral saws.

## Type 180-SA - Bright Finish High-Speed Steel - Left - Hand Cut

- Can cut material Up to 1" thick.
- Left hand spiral, Right hand cut.
- For use in Rotozip Spiral saws.
- Cuts a variety of materials from wood to fiberglass.

	TYPE 180-GP	DRYWALL BITS	
Part No	Diameter Inches	Overall Length Inches	Qty per/pack
68000	1/8"	2-1/4"	8
68020	5/32"	2-1/4"	10
68070	1/4"	2-7/8"	2

# Part a



High quality auger bits with hex shanks

produced from alloy tool steel.

 For deep drilling wood applications, quickly and easily drill holes in all types of wood products.



111 2 000 0				
Part #	Flute Length	Description of Sizes	P	
53200	5"	3/8"	53	
53210	5"	1/2"	53	
53220	5"	9/16"	53	
53230	5"	5/8"	53	
53240	5"	11/16"	53	
53250	5"	3/4"	53	
53260	5"	7/8"	53	
53270	5"	15/16"	53	
53280	5"	1"	53	
53290	5"	1-1/8"	53	

**TYPE 950** 

9'

TYPE 951 16"				
Part #	Flute Length	Description of Sizes		
53300	12"	3/8"		
53310	12"	1/2"		
53320	12"	9/16"		
53330	12"	5/8"		
53340	12"	11/16"		
53350	12"	3/4"		
53360	12"	7/8"		
53370	12"	15/16"		
53380	12"	1"		
53390	12"	1-1/8"		

TYPE 952 18"

TYPE 953 24"

Part #	Flute Length	Description of Sizes	Part #	Flute Length	Description of Sizes
53400	14"	3/8"	53500	18"	3/8"
53410	14"	1/2"	53510	18"	1/2"
53420	14"	9/16"	53520	18"	9/16"
53430	14"	5/8"	53530	18"	5/8"
53440	14"	11/16"	53540	18"	11/16"
53450	14"	3/4"	53550	18"	3/4"
53460	14"	7/8"	53560	18"	7/8"
53470	14"	15/16"	53570	18"	15/16"
53480	14"	1"	53580	18"	1"
53490	14"	1-1/8"	53590	18"	1-1/8"



Gold oxide treated body and clearance for maximum lubricity.

## Type 180-SA

It is recommended for non-ferrous metals wood and fiberglass.

YWALL BITS	S		TYPE 180-SA	DRYWALL BITS	
Overall ength Inches	Qty per/pack	Part No	Diameter Inches	Overall Length Inches	Qty per/pack
2-1/4"	8	68030	1/8"	2-1/4"	8
2-1/4"	10	68040	5/32"	2-1/4"	2
2-7/8"	2				

CAUTION: Safety glasses and dust mask must be worn at all times when using super Drywall bits.

Proudly Manufactured in the U.S.A • America's Finest High Speed Steel Cutting Tools<sup>™</sup> • Call Toll Free with globally sourced material **1.800.328.4655** 

