

# Specialty Tools

## ACRYLIC, HARD STEEL, SHEETERS DRILLS & CUTTING TOOL LUBRICANT

### Type 183-AG

Acrylic Drills with Chipfree™ Point Magnum Super Premium

- Super **CHIPFREE™** point is precision ground at a 60° angle for gradual penetration to avoid cracking and chipping of the acrylic material.
- Special 0° rake angle on cutting edge eliminates "grabbing" when drill breaks through plastic, acrylic, or laminate surfaces.
- All sizes over 1/4" have 1/4" shanks.



Part No.	Diameter Inches	Overall Length Inches	Flute Length Inches	Qty. per/pack
32260	3/32	2-1/4	1-5/16	12
31500	1/8	2-1/2	1-3/8	12
31510	5/32	2-7/8	2-3/16	12
31520	3/16	3-3/16	2	12
32220	7/32	3-3/4	2-9/16	12
31530	1/4	3-9/16	2-5/16	12
32240	9/32	3-9/16	2	12
31540	5/16	3-5/16	2-3/16	6
32290	11/32	4-1/32	2-3/8	6
31550	3/8	3-5/8	2-9/16	6
32460	13/32	4-1/32	2-3/4	6
31560	7/16	4	2-15/16	6
32470	15/32	4-7/8	3-1/8	6
31570	1/2	4-1/4	3-1/4	6

### Type 224

Sheeters Drill - Black Surface Treated

Heavy-duty 135° split point high-speed steel drill is excellent for drilling sheet metal and corrugated construction panels.



Part #	Diameter Wire Gauge	Overall Length Inches	Flute Length Inches	Qty. per/pack
27010	1	3	1-5/16	12
27030	1	4-1/2	1-5/16	12
27040	1	6	1-5/16	12

### Type 600

Flex Shaft Drill Bits - Installer Drill Bits/Wire Fishing Drill Bits

Flexible steel drill bits used for installing wire or cable

- Self feeding lead screw point and fishing eye
- Special 3/16" flexible shaft
- Drill bit penetrates wood effortlessly
- Shaft designed with flex memory retention and maximum torque translation

#### FRACTIONAL

Part #	Diameter / Overall Length	Shank Length	Qty. per/pack
89610	3/8" x 54"	3/8	1
89611	3/8" x 72"	3/8	1
89620	1/2" x 54"	3/8	1
89621	1/2" x 54"	3/8	1
89630	9/16" x 54"	3/8	1
89631	9/16" x 72"	1/4	1
89640	3/4" x 54"	1/4	1
89641	3/4" x 72"	1/4	1

### Type 602

Hard Steel Drills Carbide Tipped, Straight Flute

- These drills are made for use in drilling hardened steel in the range of **48 to 65 Rockwell C**.
- Used for drilling broken studs, springs, bolts, die sections, broken easy outs, extra tough or exotic metals, and brake drums.



Part No.	Diameter Inches	Shank Diameter Inches	Overall Length Inches	Qty. per/pack
32300	1/8	1/8	2-3/4	1
32310	5/32	5/32	3	1
32320	11/64	11/64	3	1
32330	3/16	3/16	3	1
32340	7/32	7/32	4	1
32350	1/4	1/4	4	1
32360	1/4	1/4	6	1
32370	9/32	9/32	4	1
32380	5/16	1/4	4	1
32390	5/16	5/16	6	1
32400	3/8	1/4	4	1
32410	3/8	3/8	6	1
32420	7/16	3/8	6	1
32430	1/2	1/2	6	1
32440	9/16	1/2	6	1
32450	5/8	1/2	6	1

## CUTTING TOOL LUBRICANT

### Type 11-AG

Ultra S/P™ Super Premium

High Viscosity.

- Super concentrated no run formula.
- Clings to vertical surfaces for continual lubrication.
- Virtually smoke free in even the most heat prone applications.
- Contains no ozone depleting substances.



*This fluid will extend tool life and yield a super machined finish.*

#### TYPE 11-AG ULTRA S/P™

Part No.	Size MM	Bottles Per Case	Weight Per Case
96050	12 - 4 OZ.	12	4.4 Lbs./2 Kgs.
96060	48 - 4 OZ.	48	18 Lbs./8.2 Kgs.
96070	12 - 16 OZ.	12	15 Lbs./6.8 Kgs.

**Part No. 96071** is a self selling display with an attractive attention getting decal applied to the inside of the display flap. Dispose of display when empty.